

SPECIFICATION

Rear Access Display Cube

Model	C/E-PH605	C/E-PH705
Resolution	1920x1080	
DMD Chip	0.95" LVDS DMD	
Screen Size	60 inches	70 inches
Projector Brightness	1200lm	
Contrast Ratio	2200:1	
Uniformity	95%	
LED Lifetime ^{*1}	100,000 hours	
LED Configuration	3x6	
Screen Type	Resin screen	
Viewing Angle	Horizontal: >160 degrees Vertical: >150 degrees	
Half Gain Viewing Angle	Horizontal: 38 degrees Vertical: 21 degrees OR Horizontal: 36 degrees Vertical: 34 degrees	
Gap ^{*2}	0.2mm	
Protection Level	IP6X	
Signal Input	VGA/DVI-D×2, CVBS×2	
Loop Out	DVI-D	
Control	RS232 in(DB9)x1 , RS232in(RJ45)x1 , RS232out(RJ45)x1, Remote control	
Power Supply	1+1 redundant power supply(optional)	
Power	100-240V / 50-60Hz	
Power Consumption	Bright mode: 280W Normal mode: 240W ECO mode: 180W	
Heat Dissipation	Bright mode: 955 Btu/h Normal mode: 919 Btu/h ECO mode: 614 Btu/h	
Working Temperature	0-35 °C , recommended 23+/-5 °C	
Working Humidity	30%-80%(Non-condensing)	
Product Dimension	1335mmx750mm×768mm	1548mmx870.5mmx898mm
Certificate	CCC,CE,CB,ROHS	

Remarks: The above specifications are subjected to change without prior notice.

1. The performance of LED lifetime varies in different actual working conditions.
2. The screen gap varies in different screen types and actual working conditions.